




Uf2™ | Primera®



Uf2™ | Primera® offers classic leather styling with a soft nappa feel. Built to last, this Value offering delivers a dependable polyurethane option for various upholstery applications. This tried and true essential provides endless versatility, offering an array of color choices that invites you to create a masterpiece within budget.



General Specifications

Composition:

100% Polyurethane Surface
55% Viscose Rayon, 45% Polyester

Weight:

Approx. 12.5 oz. Per Square Yard
Approx. 424 Grams Per Square Metre

Thickness:

Approx. 1.0 Millimetres

Width:

54 Inches / 137 Centimetres

Abrasion:

ASTM D4157 / 400,000 Double Rubs (Wyzenbeek)*
ASTM D3884 / 2,000 cycles (Taber)*
BS 2543 / 200,000 Rubs (Martindale)*
*meets or exceeds

Hydrolysis:

7 Weeks
ISO 1419 Method C (Accelerated Ageing)

Adhesion of Coating:

ASTM D751

Tear Strength:

ASTM D2261

Breaking Strength:

ASTM D5034

Crocking:

AATCC 8, Class 4-5 Wet & Dry

Light:

AATCC 16.3, 200 Hours, Grade 4-5

F/R Rating:

ASTM E84 (Adhered) - Class A
CA TB 117-2013 - Pass
FMVSS 302 & 95/28 Annex IV - Pass
NFPA 260 - Class 1
UFAC - Class 1

Please Note: These fabrics, when treated and/or used with other compatible furniture components, have been shown to perform well under the fire test conditions of:

- ASTM E84 (Unadhered)
- California Technical Bulletin 133
- NFPA 701

Cleaning Instructions

Only use:

- Mild soap and water to remove stains.
- Alcohol-based solutions such as Fantastik® and Formula 409®.
- 5:1 water/bleach solution to disinfect.
- Water to rinse off cleaning solutions.

Environmental Information

- Compliant with Prop 65
- Low VOCs (Volatile Organic Compounds)
- No Conflict Minerals
- No Flame Retardants (ex. Halogenated, Brominated)
- No PBDEs (Polybrominated Diphenyl Ethers)
- No Plasticizers, Heavy Metals or Phthalates
- No POPs (Persistent Organic Pollutants)
- No PVC (Polyvinyl Chloride)