



Ultraleather® | Pro



Ultraleather® | Pro is crafted with passion and purpose. Imbued with optimal durability, protection and ease of care attributes, **Pro** maintains the **Ultraleather®** reputation as the softest polyurethane fabric in its class. Combined with a classic look highlighted by a well-balanced mix of color options, **Pro's** enduring construction is the preferred high-performance choice for the most active settings.

The reasons as to why **Pro** sits at the top of so many project lists include:

- Enduring performance (14+ weeks hydrolysis results)
- Mishaps happen - in the form of ballpoint pens, red wine, mustard, denim dyes, and iodine-based stains often encountered in the healthcare sector. Stains are a thing of the past thanks to this innovative repellency
- Inherent EPA-registered antimicrobial protection for added benefit
- Engineered to out-perform the highest levels of abrasion resistance
- Ease of care

Pro is infused with power and comfort combined, taking durability and luxury to the next level.



Antimicrobial



Ink and Stain Resistant



Performance Plus



Custom

Ultraleather® | Pro

General Specifications

Composition:

100% Polyurethane Surface
100% Reinforced Rayon Backing

Weight:

Approx. 9.7 oz. Per Square Yard
Approx. 330 Grams Per Square Metre

Thickness:

Approx. 0.95 Millimetres

Width:

54 Inches / 137 Centimetres

Performance

Abrasion:

ASTM D4157 / 500,000 Double Rubs (Wyzenbeek)*
BS 2543 / 200,000 Rubs (Martindale)*

*meets or exceeds

Hydrolysis:

14+ Weeks
ASTM D3690-02 SECT. 6.11 (Hydrolytic Stability)
ISO 1419 Method C (Accelerated Ageing)

Adhesion of Coating:

ASTM D751

Tear Strength:

ASTM D2261

Breaking Strength:

ASTM D5034

Antimicrobial:

ASTM E2180

Colorfastness

Light Fastness:

AATCC 16.3, 200 Hours, Grade 4-5

Crocking:

AATCC 8, Class 5 Wet & Dry

Flammability

F/R Rating:

- ASTM E84 (Adhered) - Class A
- CA TB 117-2013 - Pass
- FMVSS 302 & 95/28 Annex IV - Pass
- NFPA 260 - Class 1
- UFAC - Class 1

Other Tests*:

- ASTM E84 (Unadhered)
- BS 5852 PT 0, 1 & 5 (Crib 5)
- BS 5867 Part 2 Type B
- BS 7175
- California Technical Bulletin 133
- FAR Specifications
- IMO A.652 (16)
- NFPA 701

*These fabrics, when treated and/or used with other compatible furniture components, have been shown to perform well under these fire test conditions.

Earth Friendly

• GREENGUARD Certified

- Meets stringent VOC emission standards
- Promotes healthier indoor air quality
- Contributes to LEED™ and BIFMA level® credits
- Compliant with Prop 65
- No Conflict Minerals
- Less than 100 ppm of antimicrobial treatment
- No Flame Retardants (ex. Halogenated, Brominated)
- No PBDEs (Polybrominated Diphenyl Ethers)
- No Plasticizers, Heavy Metals, Stabilizers, Phthalates or Bisphenol A (BPA)
- No POPs (Persistent Organic Pollutants)
- No PVC (Polyvinyl Chloride)
- No toxic by-products
- Over 99% of solvents recaptured and recycled

Ultraleather® | Pro resists:



Ballpoint ink



Betadine



Blood



Denim*



Mustard/ketchup



Red Wine

*Removal of denim dye may vary depending on the period of time the stain sets in. While Pro offers excellent protection, full removal is not guaranteed.

For more information on our fabrics, cleaning and care instructions, please visit our website.



PRODUCT
CERTIFIED FOR
LOW CHEMICAL
EMISSIONS:
UL.COM/GG
UL2818

Ultrafabrics® and logo, and Ultraleather® are trademarks of Ultrafabrics, LLC. Made in Japan.

www.ultrafabricsllc.com



2/16